



GRANITE

CONSTRUCTION	Textured Hi-Low Scroll
FIBRE TYPE	Stainproof SDX & Stainproof Eco SDX (Solution Dyed Nylon)
RECYCLED CONTENT	Face Fibre (Certain Colours) NexBac Eco (on request only)
USE CLASSIFICATION	Heavy Commercial
PILE HEIGHT	2 to 5.5mm
TOTAL THICKNESS	±7mm
TOTAL MASS	±4265g/m ² **
STANDARD SIZING AVAILABLE	50cm x 50cm***
STITCHES/10cm	36
FIRE INDEX	2 (SANS 10177-IV)
COLOUR FASTNESS TO:	
i) Light	7 (ISO 105 - B02)
ii) Rubbing	(a) Wet 4-5 (ISO 105 - X12)
Rubbing	(a) Dry 4-5 (ISO 105 - X12)
iii) Water	4 (ISO 105 - E01)
ELECTROSTATIC PROPENSITY	Less than 2.0kV (ISO 6356 & EN 1307)
STATIC CONTROL	Permanent
VOC TESTED	Pass

** Weighted average

*** Available in 50 x 50cm, 60 x 60cm, 1m x 1m NexBac tiles and 25cm x 100cm NexBac Plank tiles. As these sizes are not standard, minimum production quantities apply. Please contact your nearest Vanguard Agent for more information.

**** This Tufted Colour Placement range is a Stainproof SDX (Solution Dyed Nylon) product, available with the dimensionally stable backing system, EOS BAC, which offers sound absorption and sound reduction properties, and is also environmentally friendly.