

ELEMENTS

Technical Details



CONSTRUCTION	Tufted Colour Placement
YARN TYPE	Stainproof SDX & Stainproof SDX ECO
RECYCLED CONTENT	Yarn - certain colours
BACKING TYPE	Bitumen or ECOBAC
MACHINE GAUGE	1/10"
STITCH RATE	50st per 10cm
FINAL PILE HEIGHT BITUMEN	±5.5mm
FINAL PILE HEIGHT ECOBAC	±6.5mm
TOTAL MASS BITUMEN TILE	±3832 g/m ²
TOTAL MASS ECOBAC TILE	±4052 g/m ²
TOTAL THICKNESS BITUMEN	±5.5mm
TOTAL THICKNESS ECOBAC	±6.5mm
USE CLASSIFICATION	Commercial
DIMENSIONS	500 x 500mm
IMPACT NOISE	18dB
COLOUR FASTNESS TO:	Light: ISO 105 B02 Rubbing: (a) Wet ISO 105 X 12 Rubbing: (b) Dry ISO 105 X 12 Water: 4-5 (ISO 105-E01)
ELASTROSTATIC PROPENSITY	Less than 2.0KV (ISO 6356)
STATIC CONTROL	PERMANENT
VOC	Passed

