



# FLAGSTONE

## Technical Details

Type of Flooring	Heterogenic PVC
Type of installation	Dry Back (Stick Down)
Size of square	1000mm x 500mm
Total thickness	2.5mm
Wear layer	0.55mm
Bevelled Edges	Yes - micro bevel
Application	Heavy Commercial
Planks per carton	8
Quantity per Box	4sqm
Abrasion Resistance	Group T
Fire	EN 13501-1
Slip Resistance	DIN 51130
Underfloor Heating	Yes < 27°C
Castor Chair	Pass - soft non staining wheels
Stain & Chemical Resistance	Excellent
Warranty	10 year Commercial
VOC Compliant	ASTM method, D55116 -10- Pass
Embossing	Stone emboss



© Vanguard Collection (Pvt) Ltd.

Warranty & guarantee subject to limitations and conditions. For details contact a Vanguard agent or visit our website - [www.vanguardcollection.co.za](http://www.vanguardcollection.co.za)

### JOHANNESBURG

9 Voyager Street, Linbro Business Park, Sandton  
 PO Box 1628, Gallo Manor, 2052  
 Tel: +27 11 608 4270  
 Email: [infoJhb@vanguardcollection.co.za](mailto:infoJhb@vanguardcollection.co.za)

### CAPE TOWN

CNR Caledon & Harrington Streets, Cape Town  
 PO Box 15400, Vlaeberg, 8018  
 Tel: +27 21 464 4320  
 Email: [infoCpt@vanguardcollection.co.za](mailto:infoCpt@vanguardcollection.co.za)

These specifications are a guide only. For details on products and colours, contact your Vanguard agent.

[www.vanguardcollection.co.za](http://www.vanguardcollection.co.za)